http://www.ktuonline.com

APJ ABDUL KALAM TECHNOLOGICAL UNIVERSITY

SECOND SEMESTER M.TECH DEGREE EXAMINATION APRIL-MAY 2017

MECHANICAL ENGINEERING (MACHINE DESIGN)

01ME 6104 DESIGN OF PRESSURE VESSELS AND PIPING

Max. Marks: 60

Time: 3 Hours

Answer any two full questions from Part A, B & C

PART A

- 1) (a) Derive the relation for dilation in thin cylindrical and spherical pressure vessels (3 marks)
 - (b) Discuss the modes of failure in an ellipsoidal head to a cylindrical pressure vessel and suggest suitable remedial steps (2 marks)
 - (c) Sketch and explain the stresses near the shell and end closure junction (4 marks)
- Derive the expression for hoop stress and radial stress for thick walled cylinders subjected to internal and external pressure and also obtain expression for radial displacement (9 marks)
- (a) A thick cylinder of internal and external radii 300 mm and 500 mm respectively is subjected to a gradually increasing internal pressure. Determine the value of pressure when
 - Material of the cylinder first commences to yield
 - ii. Material yielded up to middle of cylinder
 - iii. Cylinder material suffers complete collapse. Yield strength- 600 MN/m² (6 marks)
 - (b) Sketch the hoop stress and radial stress variation across the thickness of a built up cylinders (i) at the end of shrink fit (b) after applying internal pressure (3 marks)

PART B

- 4) A horizontal vessel 6 m long with hemispherical heads and 2 m diameter is subjected to 2.5 MPa pressure. It is supported on two saddles of 120° separated by 4 m. The vessel carries an operating weight of 60 tonnes. Allowable stress (shell and support) 110 MPa. Design the vessel and supports. Provide sketches (9 marks)
- 5) Design a tall vertical pressure vessel with skirt support for the following data: Shell inside diameter: 1.8 m, shell overall height: 45m, skirt height: 3 m. Wind load: top section- 4000 N/m(32-48m), middle section: 3000 N/m(16-32m), bottom section: 2000 N/m (0-16m). Approximate Dead weight: section 2: 40 Tonnes, section 3: 70 Tonnes, bottom of vessel: 115 Tonnes, base: 125 Tonnes, Design pressure: 2 MPa, Design temperature: 50°C, Allowable stress (Shell, Skirt): 100 MPa (9 marks)
- 6) (a) Design reinforcement for the nozzle opening in a cylindrical shell for the following data: Outside diameter of shell: 2.2 m, Max. Working pressure: 30 kgf/cm², shell wall thickness: 45 mm, Corrosion allowance 3 mm, Allowable stress (shell and nozzle) 1080 kgf/cm², outside diameter of nozzle: 220 mm, nozzle wall thickness: 20 mm, length of nozzle above surface: 100 mm, No protrusion of nozzle inside the shell, allowable stress: 960 kgf/cm² (pad), Mill tolerance is 12.5% (7 marks)
 - (b) Briefly Explain the seismic loading distribution adopted for design of pressure vessels (2 marks)

http://www.ktuonline.com

PART C

- 7) (a) What is meant by pressure temperature rating? What are its classification under ASME codes (2 marks)
 - (b) Sketch and explain classification of flanges based on facings (4 marks)
 - (c) Check whether schedule 40 pipe thickness is sufficient for 6" NB pipe subjected to an external pressure of 30 bars at 400 °C. Mill tolerance is 12.5% and corrosion allowance is 1.6 mm. Factor of safety is 4. Spacing to diameter ratio is 30. If not, find minimum thickness required (6 marks)
- (a) Derive the minimum buckling pressure relation for a long thin cylindrical shell under external pressure (10 marks)
 - (b) Discuss effect of plastic yielding and initial non circularity on the buckling pressure (2 marks)
- 9) (a) Find the allowable displacement stress range for a pipe line operated in a 6 hour cycle every 24 hours. The life span of the plant is 20 years. The operating temp is 300°C and pipe material is ASTM A 106 Gr. B. Allowable stress at room temperature is 138 MPa and at operating temperature is 120 MPa. The stress range reduction factor is 0.7. (3 marks)
 - (b) Explain quick method of flexibility analysis of piping systems in case of a two anchor point uniform size piping system with no intermediate restraints (6 marks)
 - (c) Explain guided cantilever method in expansion loops to increase flexibility of piping systems (3 marks)

http://www.ktuonline.com

http://www.ktuonline.com

Whatsapp @ 9300930012 Your old paper & get 10/-पुराने पेपर्स भेजे और 10 रुपये पार्ये, Paytm or Google Pay से